







Longse Speed Dome Camera List









V202007A

AI Tracking Speed Dome Camera




Product Show	Chief Characteristics	Model No.	Specification
 <p>AI PTZ</p>	<ul style="list-style-type: none"> ★Pan/Zoom Bullet Camera ★Weatherproof Outdoor IP66 ★35μx 6PCS IR LEDs, ★Tracking effective range: 3-15M ★Pan Range: 0°~200°, Pan Speed: 30°/sec ★Tilt Range: -45°~40°, Tilt Speed: 25°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, Support ★P2P Support ★Lightning Protection: Transient Voltage 6000V ★Support Two-Way Audio ★Size of Package (LxWxH): 39.6x19.6x16(cm) ★Weight: 3 Kgs 	PTDKIHSL200	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516C, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/ M-JPEG Compression (Power Consumption ≤15Watts) Smart Analytics: Human Tracking、Intrusion Detection、Alarm Detection Board Lens 4mm With Internal POE +USD8 With External POE +USD5.5</p>
 <p>AI PTZ</p>	<ul style="list-style-type: none"> ★4.5" 18X AI Tracking IP PTZ ★Weatherproof Outdoor IP66 ★30μx 6PCS IR LEDs, IR Range: 60M ★Tracking effective range: 5-45M Speed: 3-12KM/h ★Pan Range: 0°~360°, Pan Speed: 120°/sec ★Tilt Range: 0°~93°, Tilt Speed: 30°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, Support ★P2P Support ★Power Adaptor: DC12V/3A ★Lightning Protection: Transient Voltage 6000V ★Support Two-Way Audio ★Size of Package (LxWxH): 18.5x 18.5 x 28.8 (cm) ★Weight: 2.2 Kgs 	PT4A18XIHSL200	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516C, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/ M-JPEG Compression With Internal POE +USD8 With External POE +USD5.5 (Power Consumption ≤15Watts) Smart Analytics: 3D Human Tracking、Intrusion Detection、Alarm Detection 18X Optical Zoom</p>
 <p>AI PTZ</p>	<ul style="list-style-type: none"> ★6" 18X AI Tracking IP PTZ ★Weatherproof Outdoor IP66 ★7PCS IR LEDs, 2 laser lights, IR Range 120M ★Tracking effective range:5-80M Speed: 3-12KM/h ★Pan Range: 0°~360°, Pan Speed: 80°/sec ★Tilt Range: 0°~93°, Tilt Speed: 60°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, Support ★P2P Support ★Power Adaptor: DC12V/4A ★Lightning Protection: Transient Voltage 6000V ★Support Two-Way Audio ★Size of Package (LxWxH): 25.5 x 21.5 x 41.0 (cm) ★Weight: 5Kgs 	PT6A18XIHSL200	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516C, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/ M-JPEG Compression (Power Consumption ≤20Watts) Smart Analytics: 3D Human Tracking、Intrusion Detection、Alarm Detection 18X Optical Zoom (f=5.35mm-96.3mm)</p>

HD-IP Speed Dome Camera


Product Show	Chief Characteristics	Model No.	Specification
 <p>ONVIF</p>	<ul style="list-style-type: none"> ★5" HD-IP Medium Speed Dome Camera ★Weatherproof Outdoor IP66 ★42x6PCS IR LEDs, IR Range: 120m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★Pan Speed: 45°/sec; Tilt Speed: 30°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, FTP, RTSP Support ★P2P Support ★Power Adaptor: DC12V 2A/3A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 28.5x18.5x18.5(cm) ★Weight: 2.5Kgs ★58*36.5*59.5CM 6PCS/CTN 	PT5A022HSL200	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 (Power Consumption ≤15.4Watts) 22X Optical Zoom (f=3.9mm-85.5mm)</p>
		PT5A022SS500	<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516E, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 (Power Consumption ≤15.4Watts) 22X Optical Zoom (f=3.9mm-85.5mm)</p>


 	<ul style="list-style-type: none"> ★5.5" HD-IP High Speed Dome Camera ★Weatherproof Outdoor IP66 ★7PCS Array IR LEDs + 2PCS Laser Lamp , IR Range: 150m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★Pan Speed: 120°/sec; Tilt Speed: 60°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, FTP, RTSP Support ★P2P Support ★Power Adaptor: DC12V 2A/3A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 25x21.5x41(cm) ★Weight: 4.9Kgs ★53*42*47CM 4PCS/CTN 	<p>PT5E122HSL200</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression 22X Optical Zoom (f=3.9mm-85.5mm)</p>
 	<ul style="list-style-type: none"> ★7" HD-IP High Speed Dome Camera ★Weatherproof Outdoor IP66 ★42x6PCS IR LEDs + 2PCS LED Laser, IR Range: 120m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★Pan Speed: 120°/sec; Tilt Speed: 30°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, FTP, RTSP Support ★P2P Support ★Power Adaptor: DC12V/4A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 31x31x44(cm) ★Weight: 10.7Kgs ★65*34*47CM 2PCS/CTN 	<p>PT7K122HSL200</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression 22X Optical Zoom (f=3.9mm-85.5mm)</p>
		<p>PT7K136SP200</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor, Hisilicon Hi3516A, WDR, 3D NR Super Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression 36X Optical Zoom (f=4.6mm-165mm)</p>
		<p>PT7K120SS500</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516E, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression 20X Optical Zoom (f=4.7mm-94mm)</p>
		<p>PT7K136SS500</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516A, WDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression 36X Optical Zoom (f=4.6mm-165mm)</p>
 	<ul style="list-style-type: none"> ★7" HD-IP High Speed Dome Camera ★Weatherproof Outdoor IP66 ★42x8PCS IR LEDs, IR Range: 120m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★Pan Speed: 120°/sec; Tilt Speed: 60°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, FTP, RTSP Support ★P2P Support ★Power Adaptor: DC12V/4A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 31x31x44(cm) ★Weight: 10.2Kgs ★65*34*46CM 2PCS/CTN 	<p>PT7E122HSL200</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 (Power Consumption ≦30Watts) 22X Optical Zoom (f=3.9mm-85.5mm)</p>
		<p>PT7E136SP200</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor, Hisilicon Hi3516A, WDR, 3D NR Super Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 (Power Consumption ≦30Watts) 36X Optical Zoom (f=4.6mm-165mm)</p>
		<p>PT7E120SS500</p>	<p>1/2.8" Sony 5.1MP High Performance CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Main Stream: 5MP@15fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 (Power Consumption ≦30Watts) 20X Optical Zoom (f=4.7mm-94mm)</p>
		<p>PT7E136SS500</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516A, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 (Power Consumption ≦30Watts) 36X Optical Zoom (f=4.6mm-165mm)</p>
 	<ul style="list-style-type: none"> ★10" HD-IP High Speed Dome Camera ★Weatherproof Outdoor IP66 ★42 x 10PCS IR LEDs + 5PCS LED Laser, IR Range: 240m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~90° Flip ★Pan Speed: 200°/sec; Tilt Speed: 100°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★TCP/IP, HTTP, FTP, RTSP Support ★P2P Support ★Power Adaptor: DC12V/4A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 33x33x52(cm) ★Weight: 13.7Kgs ★68*36*55CM 2PCS/CTN 	<p>PT10G136SP200</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor, Hisilicon Hi3516A, WDR, 3D NR Super Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression 36X Optical Zoom (f=4.6mm-165mm)</p>
		<p>PT10G120SS500</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516E, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression 20X Optical Zoom (f=4.7mm-94mm)</p>
		<p>PT10G136SS500</p>	<p>1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516A, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression 36X Optical Zoom (f=4.6mm-165mm)</p>


Mini IP PTZ Camera

Product Show	Chief Characteristics	Model No.	Specification
	<ul style="list-style-type: none"> ★ 2.5" HD-IP Mini Dome Camera ★ Weatherproof Outdoor IP67 ★ 35x4PCS IR LEDs, IR Range: 45m ★ Pan Range: 0°~350° Continue; Tilt Range: 0°~70° Flip ★ Pan Speed: 25°/sec; Tilt Speed: 20°/sec ★ Preset Points: 220 ★ TCP/IP, HTTP, FTP, RTSP Support ★ P2P Support ★ TVS3000V Lighting Protection, Surge Protection and Voltage Transient Protection ★ Size of Package (LxWxH): 14x14x13(cm) ★ Weight: 1.1Kgs ★ 32*32*47CM 10PCS/CTN 	PTDA4XHSL200	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression Add USD3 for Plastic Wall Bracket (0.8Kgs) Add USD5 for Metal Wall Bracket (1Kgs) With Internal POE (Power Consumption ≦ 15.4Watts) 4X Optical Zoom (f=2.8mm-12mm)
		PTDA4XSS500	1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516E, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression Add USD3 for Plastic Wall Bracket (0.8Kgs) Add USD5 for Metal Wall Bracket (1Kgs) With Internal POE (Power Consumption ≦ 15.4Watts) 4X Optical Zoom (f=2.8mm-12mm)
	<ul style="list-style-type: none"> ★ HD-IP Pan/Zoom Bullet Camera ★ Weatherproof Outdoor IP66 ★ 35μx6PCS IR LEDs, IR Range: 80m ★ Pan Range: 0°~180°, Pan Speed: 30°/sec ★ Tilt Range: -45°~40°, Tilt Speed: 25°/sec ★ Preset Points: 220 ★ Guard Tours: 3 Groups ★ Guard Points: Max.16 points ★ TCP/IP, HTTP, FTP, RTSP Support ★ P2P Support ★ Lightning Protection: Transient Voltage 6000V ★ Size of Package (LxWxH): 39.6x19.6x16(cm) ★ Weight: 3Kgs ★ 68*41*62CM 12PCS/CTN 	PTDK4XHSL200	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor Hisilicon Hi3516E, DWDR, 3D NR Starlight Main Stream: 1080P@30fps; With IR-CUT H.265/H.264 Compression Method With Internal POE +USD8 With External POE +USD5.5 (Power Consumption ≦ 15.4Watts) 4X Optical Zoom (f=2.8mm-12mm)
		PTDK4XSS500	1/2.8" SONY Starvis Back-illuminated CMOS sensor Hisilicon Hi3516E, DWDR, 3D NR Main Stream: 5MP@30fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 With External POE +USD5.5 (Power Consumption ≦ 15.4Watts) 4X Optical Zoom (f=2.8mm-12mm)
	<ul style="list-style-type: none"> ★ HD-IP Pan/Zoom Bullet Camera ★ Weatherproof Outdoor IP66 ★ 4PCS Array IR LEDs + 2PCS Laser Lamp, IR Range: 100m ★ Pan Range: 0°~180°, Pan Speed: 30°/sec ★ Tilt Range: -45°~40°, Tilt Speed: 25°/sec ★ Preset Points: 220 ★ Guard Tours: 3 Groups ★ Guard Points: Max.16 points ★ TCP/IP, HTTP, FTP, RTSP Support ★ P2P Support ★ Lightning Protection: Transient Voltage 6000V ★ Size of Package (LxWxH): 39.6x19.6x16(cm) ★ Weight: 3Kgs ★ 68*41*62CM 12PCS/CTN 	PTDK10XHSL200	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor Hisilicon Hi3516C, DWDR, 3D NR Main Stream: 1080P@30fps; With IR-CUT With Internal POE +USD8 With External POE +USD5.5 (Power Consumption ≦ 15.4Watts) 10X Optical Zoom (f=5.1mm-51mm)
		PTDK10XSS500	1/2.5" Aptina 5.1MP High Performance CMOS Sensor Hisilicon Hi3516D, DWDR, 3D NR Main Stream: 5MP@15fps; With IR-CUT H.265/H.264 Compression With Internal POE +USD8 With External POE +USD5.5 (Power Consumption ≦ 15.4Watts) 10X Optical Zoom (f=5.1mm-51mm)




3 IN1 HD Speed Dome Camera

Product Show	Chief Characteristics	Model No.	Specification
	<ul style="list-style-type: none"> ★ 5" Medium Speed Dome Camera ★ 3IN1: AHD/HD-TVI/CVBS ★ Weatherproof Outdoor IP66 ★ 42x6PCS IR LEDs, IR Range: 80m ★ Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★ Pan Speed: 45°/sec; Tilt Speed: 30°/sec ★ Preset Points: 220 ★ Guard Tours: 3 Groups ★ Guard Points: Max.16 points ★ RS485, Pelco D/P Support ★ OSD Menu Available ★ Power Adaptor: DC12V 2A/3A ★ Lightning Protection: Transient Voltage 6000V ★ Size of Package (LxWxH): 29.5x28x17(cm) ★ Weight: 4.2Kgs ★ 58*36.5*59.5CM 6PCS/CTN 	PT5A018HTC200NS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, DNR 18X Optical Zoom (f=5.35mm-96.3mm)




	<ul style="list-style-type: none"> ★7" High Speed Dome Camera ★3IN1: AHD/HD-TVI/CVBS ★Weatherproof Outdoor IP66 ★ 42x6PCS IR LEDs + 2PCS Laser Lamp, IR Range: 120m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★Pan Speed: 120°/sec; Tilt Speed: 30°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★RS485, Pelco D/P Support ★OSD Menu Available ★Power Adaptor: DC12V/4A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 31x31x44(cm) ★Weight: 10.7Kgs ★65*34*47CM 2PCS/CTN 	PT7K118HTC200NS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, DNR 18X Optical Zoom (f=5.35mm-96.3mm)
		PT7K133HTC200NS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, DNR 33X Optical Zoom (f=4.6mm-152mm)

	<ul style="list-style-type: none"> ★7" High Speed Dome Camera ★3IN1: AHD/HD-TVI/CVBS ★Weatherproof Outdoor IP66 ★ 42x8PCS IR LEDs, IR Range: 120m ★Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip ★Pan Speed: 120°/sec; Tilt Speed: 60°/sec ★Preset Points: 220 ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★RS485, Pelco D/P Support ★OSD Menu Available ★Power Adaptor: DC12V/4A ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 31x31x44(cm) ★Weight: 10.2Kgs ★65*34*46CM 2PCS/CTN 	PT7E118HTC200NS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, DNR 18X Optical Zoom (f=5.35mm-96.3mm)
		PT7E133HTC200NS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, DNR 33X Optical Zoom (f=4.6mm-152mm) IR Range: 150m




Mini HD PTZ Camera

Product Show	Chief Characteristics	Model No.	Specification
 	<ul style="list-style-type: none"> ★2.5" Mini Dome Camera ★3IN1: AHD/HD-TVI/CVBS ★Weatherproof Outdoor IP67 ★ 35x4PCS IR LEDs, IR Range: 60m ★Pan Range: 0°~355° Continue; Tilt Range: 0°~70° Flip ★Pan Speed: 25°/sec; Tilt Speed: 20°/sec ★Preset Points: 220 ★RS485, Pelco D/P Support ★OSD Menu Available ★TVS3000V Lighting Protection, Surge Protection and Voltage Transient Protection ★Size of Package (LxWxH): 15x15x15(cm) ★Weight: 1.1Kgs ★32*32*47CM 10PCS/CTN 	PTDAHTC2004XNS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, 3D NR Add USD3 for Plastic Wall Bracket (0.8Kgs) Add USD5 for Metal Wall Bracket (1Kgs) 4X Optical Zoom (f=2.8mm-12mm)
		PTDAHTC5004XNS	1/2.9" SONY CMOS Sensor 5MP Low Illumination, ICR, 3D NR Add USD3 for Plastic Wall Bracket (0.8Kgs) Add USD5 for Metal Wall Bracket (1Kgs) 4X Optical Zoom (f=2.8mm-12mm)
	<ul style="list-style-type: none"> ★Pan/Zoom Bullet Camera ★3IN1: AHD/HD-TVI/CVBS ★Weatherproof Outdoor IP66 ★6PCS Array IR LEDs + 2PCS Laser Lamp, IR Range: 100m ★Pan Range: 0°~180°, Pan Speed: 30°/sec ★Tilt Range: -45°~40°, Tilt Speed: 25°/sec ★Guard Tours: 3 Groups ★Guard Points: Max.16 points ★RS485, Pelco D/P Support ★OSD Menu Available ★Lightning Protection: Transient Voltage 6000V ★Size of Package (LxWxH): 39.6x19.6x16(cm) ★Weight: 3Kgs ★68*41*62CM 12PCS/CTN 	PTDKHTC20010XNS	1/2.9" SONY CMOS Sensor 2.1MP/1080P Low Illumination, ICR, 3D NR 10X Optical Zoom (f=5.1mm-51mm)

※ PTZ Control Keyboard

Product Show	Chief Characteristics	Model No.	Specification
	<ul style="list-style-type: none"> ★ONVIF 2.4 compatible ★Support auto searching IP devices ★Control Max. 253pcs IP devices in the same network segment ★Support 4D jostick, support button ★Interface: 1xRJ45, 1xRS485, 1xRS232 ★With internal POE ★Size: 320mm*179mm*61mm Weight: 3.5Kg 	SDK90	IP PTZ Controller with 4D (Pan, Tilt, Zoom, Iris) Joystick
	<ul style="list-style-type: none"> ★ONVIF 2.4 compatible ★5' colorful LED display ★Plug and Play, automatically add and distribute IP address ★3D jostick ★Support USB and HDMI output ★Size: 260mm*160mm*48mm Weight: 2.5Kg 	SDK95	IP PTZ Controller with 3D (Pan, Tilt, Zoom) Joystick
	<ul style="list-style-type: none"> ★Protocol: Pelco-P, Pelco-D ★Baud Rate(bps): 1200, 2400, 4800, 9600, 19200 ★Communication Mode: RS485 half-duplex ★3D Jostick ★Menu and Key: English ★Size: 420mm*260mm*170mm Weight: 1.3Kg 	SDK75	HD PTZ Controller with 3D (Pan, Tilt, Zoom) Joystick for Analog PTZ and AHD/HD-CVI/HD-TVI PTZ

※ PTZ Special Holder

Product Show	Chief Characteristics	Model No.	Specification
	<ul style="list-style-type: none"> ◆White Color ◆SIZE: 170(W) x 131(D) x 46(H)mm ◆Weight: 1.2Kg 	B270	Pole Holder Can be equipped with PTZ Model PT5A, PT7E
	<ul style="list-style-type: none"> ◆White Color ◆SIZE: 163(W) x 120(D) x 113(H)mm ◆Weight: 1Kgs ◆Material: Metal 	B271	Wall Mode Bracket Can be equipped with PTZ Model PTDC, PTDA
	<ul style="list-style-type: none"> ◆White Color ◆SIZE: 163(W) x 120(D) x 113(H)mm ◆Weight: 0.8Kgs ◆Material: Plastic 	B272	Wall Mode Bracket Can be equipped with PTZ Model PTDC, PTDA

Terms & Conditions

Price Terms: SAY US\$, EX-Works Guangzhou Factory

Terms of Payment: T/T, L/C, Paypal

Warranty: Two Years After Shipping Date

Attention: The unit price fluctuates according to the change of parameters and market. And the price above does not include the delivery charges or other expense.

Contact Longse



Tel : +86 20 66217333 Fax : +86 20 66217338

E-mail: sales@longse.com

Website: <http://www.longse.com>

Longse

More secure, More intelligent Facebook: <https://www.facebook.com/longse2006/>



No.728 Kaichuang Ave., Economic & Technological Development Zone, Luogang District, Guangzhou, China 510530

