













Longse


Longse **Wi-Fi IP** Camera Price List

Ver.: V202007A

Bullet Wi-Fi IP Camera					
Product Show	Chief Characteristics	Model No.	Resolution	Solution	Specification
	Bullet WIFI IP Camera Board Lens 3.6mm Water resistance: IP67 Anti-Cut 3-Axis Bracket Size: 157(W) x 70(H) x 66(D)mm Weight: 650g With Junction Box Add USD4.6	LBH30FK500W	5MP	K05 + FH8856 (H.264/H.264+) (H.265/H.265+)	1/2.5" SOI High-resolution CMOS Sensor FUHAN SOC, With IR-CUT; 5MP HD Lens Main Stream: 5MP@20fps, 4MP@25fps, 1080P@30fps With External SD Card Slot (Max.256G) Wi-Fi Range: No obstacles 300m Max. (IR LED: 42μ x 2PCS IR range: 25M)
	Bullet WIFI IP Camera Board Lens 3.6mm Water Resistance: IP67 Anti-Cut 3-Axis Bracket Size: 186(W) x 75(H) x 71(D)mm Weight: 500g With Junction Box Add USD4.6	LBF30FK500W	5MP	K05 + FH8856 (H.264/H.264+) (H.265/H.265+)	1/2.5" SOI High-resolution CMOS Sensor FUHAN SOC, With IR-CUT; 5MP HD Lens Main Stream: 5MP@20fps, 4MP@25fps, 1080P@30fps With External SD Card Slot (Max.256G) Wi-Fi Range: No obstacles 300m Max. (IR LED: 42μ x 2PCS IR range: 25M)
	IR LED: 42μ x 4PCS IR Range: 40M Board Lens 8mm 3.6mm is Optional Water Resistance: IP67 Size: 179(W) x 90(H) x 90(D)mm Weight: 1.65Kgs Wall Bracket is Optional With Junction Box Add USD6	LBE60FK5002W	5MP	K05 + FH8856 (H.264/H.264+) (H.265/H.265+)	1/2.5" SOI High-resolution CMOS Sensor FUHAN SOC, With IR-CUT; 5MP HD Lens Main Stream: 5MP@20fps, 4MP@25fps, 1080P@30fps With External SD Card Slot (Max.256G) Wi-Fi Range: No obstacles 300m Max.
Dome Wi-Fi IP Camera					
Product Show	Chief Characteristics	Model No.			Specification
	Weatherproof Dome WIFI IP Camera Water resistance: IP67 IR LED: 14μ x 24PCS IR Range: 30m Board Lens 3.6mm Size: ∅ 120 x 104(H) mm Weight: 600g (Ball Part Metal, Other Plastic) With Deep Base Add USD2.9 With Junction Box Add USD6	LIRDQFK500W	5MP	K05 + FH8856 (H.264/H.264+) (H.265/H.265+)	1/2.5" SOI High-resolution CMOS Sensor FUHAN SOC, With IR-CUT; 5MP HD Lens Main Stream: 5MP@20fps, 4MP@25fps, 1080P@30fps With Internal SD Card Slot (Max.256G) Wi-Fi Range: No obstacles 300m Max. Board Lens 8mm (3.6mm is Optional)
	Vandalproof & Weatherproof IR Dome Camera Water Resistance: IP67 IR LED: 42μ x 4PCS IR Range: 40m Board Lens 8mm 3.6mm is Optional Size: ∅136 x 148(H)mm Weight: 1.7Kgs With Wall Bracket Add USD7	LIRABFK500W	5MP	K05 + FH8856 (H.264/H.264+) (H.265/H.265+)	1/2.5" SOI High-resolution CMOS Sensor FUHAN SOC, With IR-CUT; 5MP HD Lens Main Stream: 5MP@20fps, 4MP@25fps, 1080P@30fps With External SD Card Slot (Max.256G) Wi-Fi Range: No obstacles 300m Max.
Miniature Wi-Fi IP Cameras					
Product Show	Chief Characteristics	Model No.		Solution	Specification
	Miniature WIFI IP Camera Board Lens 2.8mm Size: 36(W) x 36(H) x 33(D)mm Weight: 300g	LMBM36SL200W	2MP	IMX307 + Hi3516C (H.264/H.264+) (H.265/H.265+)	1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR Main Stream: 1080P@30fps 3MP HD Lens Wi-Fi Range: No Obstacles 100m Max. With External SD Card Slot (Max.128G) With 2-Way Audio With Alarm IN 3.3V~20V

	<p>Miniature WIFI IP Camera 3.7mm Taper Pinhole Lens Size: 36(W) x 36(H) x27(D)mm Weight: 300g</p>	LMCM36SL200W	2MP	IMX307 + Hi3516C (H.264/H.264+) (H.265/H.265+)	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR Main Stream: 1080P@30fps 3MP HD Lens Wi-Fi Range: No Obstacles 100m Max. With External SD Card Slot (Max.128G) With 2-Way Audio With Alarm IN 3.3V~20V</p>
	<p>Miniature Camera 3.7mm Pinhole Lens/82° (F2.8) Lens with 2M cable Brackets Included Size: 104(L) x 78(W) x25.8(H)mm Weight: 770g</p>	LMEMSSL2002W	2M	IMX307 + Hi3516C (H.264/H.264+) (H.265/H.265+)	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR Starlight Main Stream: 1080P@30fps 3MP HD Lens Support Micro SD Card, Max. 512G Audio I/O, Alarm I/O. 1XRS485 With Internal POE</p>
	<p>Miniature Camera 3.7mm Pinhole Lens/82° (F2.8) Lens with 8M cable Brackets Included Size: 104(L) x 78(W) x25.8(H)mm Weight: 770g</p>	LMEMSSL2008W			
	<p>Miniature Camera 3.7mm Pinhole Lens/82° (F2.8) Lens with 2M cable Two Brackets Included Size: 104(L) x 78(W) x25.8(H)mm Weight: 790g</p>	LMEMPCSL2002W	2M	IMX307 + Hi3516C (H.264/H.264+) (H.265/H.265+)	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR Starlight Main Stream: 1080P@30fps 3MP HD Lens Support Micro SD Card, Max. 512G Audio I/O, Alarm I/O. 1XRS485 With Internal POE</p>
	<p>Miniature Camera 3.7mm Pinhole Lens/82° (F2.8) Lens with 8M cable Two Brackets Included Size: 104(L) x 78(W) x25.8(H)mm Weight: 790g</p>	LMEMPCSL2008W			
	<p>Miniature Camera 2.8mm /106° (F1.6) Lens with 2M cable Two Brackets Included Size: 104(L) x 78(W) x25.8(H)mm Weight: 810g</p>	LMEMTCSL2002W	2M	IMX307 + Hi3516C (H.264/H.264+) (H.265/H.265+)	<p>1/2.8" SONY Starvis Back-illuminated CMOS Sensor HISILICON Hi3516C, WDR Starlight Main Stream: 1080P@30fps 3MP HD Lens Support Micro SD Card, Max. 512G Audio I/O, Alarm I/O. 1XRS485 With Internal POE</p>
	<p>Miniature Camera 2.8mm /106° (F1.6) Lens with 8M cable Two Brackets Included Size: 104(L) x 78(W) x25.8(H)mm Weight: 810g</p>	LMEMTCSL2008W			

Wi-Fi NVR

Product Show	Model No.	Specification
 <p>H.265/H.265+</p> <p>8CH WIFI NVR, 1 x SATA</p> <p>1 x USB, 1 x RJ-45</p> <p>5M Support</p>	NVR3608DEWS	Camera Input: 9CH 1080P@30fps/9CH 3MP@15fps/4CH 5MP@30fps Wi-Fi IP Camera
		Network Interface: 1xRJ45 (10M/100M Adaptive Ethernet Interface)
		Video Output: 1xHD Output/ 1xVGA Output
		Incoming Bandwidth: 30Mb/S(Wireless),60Mb/S(Wired)
		Compression Method: H.265/H.265+, H.264/H.264+
		Recording Resolution: 1080P/3MP/5MP
		WIFI Range: No Obstacles 300m Max.
		Preview Resolution: 9CH@D1/3CH@1080P/3CH@3MP/1CH@5M
		Playback Resolution: 1CH@5M/3CH@1080P/3CH@3MP
		Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup
		Static, Dynamic IP and DDNS, P2P, Wi-Fi , Support IE and Special Client Software
		Backup: 1xUSB2.0 (such as U Disk, USB Drive) and Network
		1 SATA Hard Disk Interface (2.5"/3.5" SATA, Up to 6TB)
Support Remote View by Smart Phone		
Dimensions (LxWxH): 260*215*43(mm) Weight: 2kg		

Terms & Conditions

Price Terms: SAY US\$, EX-Works Guangzhou Factory

Terms of Payment: T/T, L/C, Paypal

Warranty: Two Years After Shipping Date

Attention: The unit price fluctuates according to the change of parameters and market. And the price above does not include the delivery charges or other expense.

Contact Longse



Longse
 More secure, More intelligent

Tel : +86 20 66217333 Fax : +86 20 66217338

E-mail: sales@longse.com

Website: http://www.longse.com

Facebook: https://www.facebook.com/longse2006/

No.728 Kaichuang Ave., Economic & Technological Development Zone, Guangzhou, China 510530



PROFESSIONAL **IOT**
SOLUTION PROVIDER

FOCUS VIDEO AS THE CORE

Longse